SRI

GC Innovations

Multiple Gas Analyzer #1

Keep your gas products in spec! Monitor gas product purity, natural gas, and ambient air quality. Sounds expensive and complicated to operate?

Not from SRI! The SRI Multiple Gas

single injection!


Separates multiple gases with a single injection

Very tolerant of user adjustments and timing variations

Simpler than other multi-gas capable GC systems

x Multiple gas analysis in a compact unit

Analyzer #1 uses just ONE gas sampling valve and TWO analytical columns to perform the same separations that require multiple valves and columns in other systems. Best of all, the Multiple Gas Analyzer #1 can achieve ppm to 100% concentrations with a



TCD Detector - universal response, 250ppm to 100%


FID Detector - Hydrocarbon selectivity, 5ppm detection limits Methanizer in FID body- converts CO and CO₂ to Methane for FID


Programmable

Specifically Designed for Separation of Whole Gas Components and Natural Gas Samples

Multiple Gas Analyzer #1

Separating out the hydrocarbon components of natural gas facilitates accurate BTU quantification. This compositional analysis of a natural gas standard by an SRI Multiple Gas Analyzer #1 shows good separation up to the pentanes. Performing compositional analyses of natural gas product before and after refining helps to maximize process efficiency and profit.






The same instrument produced this chromatogram, separating a sample mix of 1% fixed gas standard and ethane. With the built-in PeakSimple data system, the gas sampling valve was programmed to inject the sample loop contents into the carrier gas stream at 5 seconds, then rotate back at 6 minutes, after CO elution.

The basic Multiple Gas Analyzer #1 has a TCD detector only; this model provides analyses in the 250ppm to 100% range for fixed and natural gases. A second option is a TCD, Methanizer, and FID detector combination which adds 5ppm detection limits for CO, CO₂, and all hydrocarbon peaks; this model is useful for air quality monitoring and other applications. A third

option is a TCD-HID detector combination, for detection limits in

the 10ppm range for all analytes...the HID even sees hydrogen! Since we build each GC from the boards up, the Multiple Gas Analyzer #1 may be further customized to suit your application needs. With the optional built-in "whisper-quiet" air compressor, the Multiple Gas Analyzer #1 can be used with the SRI H₃-50 hydrogen generator to separate multiple

gases anywhere, without using compressed gas cylinders!



8610-0070	Multiple Gas Analyzer #1 GC with TCD detector	\$ 9,995.00
8610-0071	Multiple Gas Analyzer #1 GC with TCD, Methanizer, FID & built-in Air Compressor	\$13,995.00
8610-0072	Multiple Gas Analyzer #1 GC with TCD & HID detectors	\$14,495.00
8690-0070	Built-in Air Compressor, 120 VAC	\$ 595.00
8690-2270	Built-in Air Compressor, 220 VAC	\$ 695.00